

# POWER TROWELS

## PRO700

www.oscar.biz.tr

<b>Model</b>	: PRO700 B - E
<b>Type</b>	: Power Trowel
<b>L x W x H - PRO700B</b>	: 1980 x 750 x 1110 mm
<b>L x W x H - PRO700E</b>	: 1980 x 750 x 1140 mm
<b>Weight</b>	: 80 – 85 kg
<b>Gearbox</b>	: Maintenance Free, Heavy – Duty
<b>Reduction</b>	: 1:19,5
<b>Clutch</b>	: Centrifugal Clutch
<b>Drive</b>	: One way V-Belt Drive
<b>Trowelling Length</b>	: 730 mm
<b>Trowelling Area</b>	: 0.44 m <sup>2</sup>
<b>Trowelling Speed</b>	: Max. 130 rpm
<b>PRO700B Gasoline</b>	: Honda GX 160 - (5,5 HP)-Recoil Starter
<b>PRO700E Electric Single Speed</b>	: 2.2 Kw 220V Three Phase

### Standard;

- \* Dead man's handle safety switch
- \* Lifting Eye
- \* Comfort Pad
- \* Grease fittings on spider
- \* Gas throttle on handle
- \* Blade pitch adjustment
- \* Carrying pipe

### Optional;

- \* Floating discs
- \* Floating blades
- \* Combined blades
- \* Bushing for spider plate
- \* Foldable arm
- \* Carrying wheels



### Consumables

Stock Code	Description
11. PD700	700 DISC 745mm 2,5mm
11. PBT700	BLADE

Stock Code	Description
10. PRO700B GX160	GASOLINE TROWEL 5,5HP HONDA
10. PRO700B GX160 KK	GASOLINE TROWEL 5,5HP HONDA-FOLDABLE HANDLE
10. PRO700B GX200	GASOLINE TROWEL 6,5HP HONDA
10. PRO700B GX200 KK	GASOLINE TROWEL 6,5HP HONDA-FOLDABLE HANDLE
10. PRO700E 2.2KW 380V	ELECTRIC TROWEL 2,2KW-THREE-PHASE

### Dimensions